







### TWENTY-SECOND ANNUAL CONFERENCE

## **YUCOMAT 2021**

Hunguest Hotel Sun Resort, Herceg Novi, Montenegro August 30 - September 3, 2021 http://www.mrs-serbia.org.rs

# Program and Book of Abstracts

Organised by: **Materials Research Society of Serbia** 

**Endorsed by: Federation of European Material Societies** 

CIP - Каталогизацијаупубликацији НароднабиблиотекаСрбије, Београд

66.017/.018(048)

#### DRUŠTVO za istraživanje materijala Srbije (Beograd). Godišnja konferencija

(22; 2021; Herceg Novi)

Programme; and the Book of abstracts / Twenty-second Annual Conference YUCOMAT 2021 Herceg Novi, Montenegro, August 30 - September 3, 2021; organised by Materials Research Society of Serbia; [editor Dragan P. Uskoković]. - Belgrade: Materials Research Society of Serbia, 2021 (Herceg Novi: Biro Konto). - XXXIII, 146 str.: ilustr.; 23 cm

Tiraž 150. - Bibliografija uz pojedine apstrakte. - Registar.

ISBN 978-86-919111-6-4

а) Наука оматеријалима-- Апстрактиб) Техничкиматеријали—Апстракти

COBISS.SR-ID 44447497

Title: THE TWENTY-SECOND ANNUAL CONFERENCE

YUCOMAT 2021

Program and Book of Abstracts

**Publisher:** Materials Research Society of Serbia

Knez Mihailova 35/IV, P.O. Box 433, 11000 Belgrade, Serbia Phone: +381 11 2185-437; hhttp://www.mrs-serbia.org.rs

**Editor:** Prof. Dr. Dragan P. Uskoković

Technical editor: Jasmina R. Jevtić

**Typesetting** 

and prepress: Dr. Aleksandar Dekanski

**Cover page:** Nenad Ignjatović

Covers: Images on front & back covers are the property of MRS Serbia

ISBN 978-86-919111-6-4

Copyright © 2021 Materials Research Society of Serbia - MRSS

MRSS is member of the Federation of European Materials Societies



**Printed in:** Biro Konto

Sutorina bb, Igalo - Herceg Novi, Montenegro

Phones: +382-31-670123, 670025, E-mail: bkonto@t-com.me Circulation: 150 copies. The end of printing: August 2021

#### TWENTY-SECOND ANNUAL CONFERENCE YUCOMAT 2021 Herceg Novi, August 30 – September 3, 2021

#### P.S.III.3.

#### Synthesis and deposition of MAPbBr<sub>3</sub> perovskite on titania nanotube arrays

Milica Stefanović<sup>1</sup>, Jelena Vujančević<sup>2</sup>, Rada Petrović<sup>3</sup>, Đorđe Janaćković<sup>3</sup>

<sup>1</sup>University of Belgrade, Innovation Center of Faculty of Technology and Metallurgy, Belgrade, Serbia, <sup>2</sup>Institute of Technical Sciences of SASA, 11000, Belgrade, Serbia, <sup>3</sup>University of Belgrade, Faculty of Technology and Metallurgy, Belgrade, Serbia

The organo-inorganic perovskites are materials that have recently revolutionized the field of photovoltaics due to their low-cost fabrication and high optical absorption. The hybrid organoinorganic perovskite absorbs the visible part of the spectrum resulting in the creation of electron-hole pair. To decrease the recombination of charge carriers, the construction of solar cells requires the existence of separate layers for holes and for electrons. TiO<sub>2</sub> is usually used as an electron transport layer because its conduction band (CB) lies under the CB of perovskite. In that way, electrons diffuse from CB of perovskite to CB of TiO<sub>2</sub>. For these experiments, TiO<sub>2</sub> nanotubular structure was used as an electron transport layer due to its advantages compared to nanoparticular TiO<sub>2</sub>. TiO<sub>2</sub> nanotubes can provide a one-dimensional transmission channel for the charge carriers, so it will reduce the recombination rate of the carriers and provide a channel for fast carrier transport. However, there is a problem with the contact surface between perovskite and TiO<sub>2</sub> nanotubes. The aim of this study is to increase the contact surface of perovskite and TiO<sub>2</sub> nanotubes by filling the nanotubes with perovskite material in order to improve electron transport. Methylammonium lead bromide perovskite (MAPbBr<sub>3</sub>) was deposited on anodically synthesized TiO<sub>2</sub> nanotubes which were annealed at 450 °C for 1 h. After degassation of the sample under high vacuum for 3 h at 200 °C, the cooled sample was put in a solution of MAPbBr<sub>3</sub> in dimethylformamide (DMF) and it was treated with inert gas (N<sub>2</sub>), which enabled the filling of the nanotubes with perovskite material to some extent. FESEM and XRD analyses were used for morphological and chemical characterization of the sample. The diffuse reflectance spectroscopy measurement of the sample proved that deposition of MAPbBr<sub>3</sub> improves the absorption properties of TiO<sub>2</sub> nanotubes. By measuring the I-V characteristics of the sample in the dark and under visible light, a hysteresis curve was obtained.