

FIFTEENTH ANNUAL CONFERENCE

YUCOMAT 2013

Hunguest Hotel Sun Resort Herceg Novi, Montenegro,
September 2-6, 2013
<http://www.mrs-serbia.org.rs>

Programme and The Book of Abstracts

Organised by:
Materials Research Society of Serbia

under the auspices of
**Federation of European Material Societies
and
Materials Research Society**

Title: THE FIFTEENTH ANNUAL CONFERENCE
YUCOMAT 2013
Programme and The Book of Abstracts

Publisher: Materials Research Society of Serbia
Knez Mihailova 35/IV, 11000 Belgrade, Serbia
Phone: +381 11 2185-437; Fax: + 381 11 2185-263
<http://www.mrs-serbia.org.rs>

Editors: Prof. Dr. Dragan P. Uskoković and Prof. Dr. Velimir Radmilović

Technical editor: Aleksandra Stojičić

Cover page: Aleksandra Stojičić and Milica Ševkušić

Copyright © 2013 Materials Research Society of Serbia

Acknowledgments:



Printed in: Biro Konto
Sutorina bb, Igalo – Herceg Novi, Montenegro
Phones: +382-31-670123, 670025, E-mail: bkonto@t-com.me
Circulation: 220 copies. The end of printing: August 2013

P.S.A.16.

SYNTHESIS OF F-DOPED LiFePO_4 VIA PRECIPITATION METHOD

M. Milović¹, F.R. Vukajlović², D. Jugović¹, M. Mitrić², B. Jokić³,
N. Cvjetičanin⁴, A.S. Milošević², Z.S. Popović², D. Uskoković¹

¹*Institute of Technical Sciences of SASA, Belgrade, Serbia,*

²*Vinča Institute of Nuclear Sciences, University of Belgrade, Belgrade, Serbia,*

³*Faculty of Technology and Metallurgy, University of Belgrade, Belgrade, Serbia,*

⁴*Faculty of Physical Chemistry, University of Belgrade, Belgrade, Serbia*

Fluorine-doped, olivine-structured LiFePO_4 suitable for cathode material in rechargeable lithium batteries was prepared by aqueous precipitation followed by high temperature treatment at 700°C under slightly reductive atmosphere ($\text{Ar}+5\%\text{H}_2$). The starting materials were equimolar quantities of $(\text{NH}_4)_2\text{HPO}_4$, $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$ and LiF . LiF served as both lithium and fluorine source. Besides the lattice parameters and the primitive cell volume reductions, compared to the undoped sample synthesized under the same conditions using LiNO_3 as lithium source, the Rietveld refinement also shows that fluorine ions preferably occupy specific oxygen sites. Particularly, the best refinement is accomplished when fluorine ions occupy O(2) sites exclusively. By means of up-to-date electronic structure and total energy calculations this experimental finding is theoretically confirmed. Such fluorine doping also produces closing of the gap in the electronic structure and consequently better conductivity properties of the doped compound. In addition, the morphological and electrochemical performances of the synthesized powders are fully characterized.

P.S.A.17.

CRYSTAL STRUCTURE REFINEMENT OF $\text{Li}_2\text{FeSiO}_4$ CATHODE MATERIAL

D. Jugović¹, M. Mitrić², M. Milović¹, B. Jokić³, D. Uskoković¹

¹*Institute of Technical Sciences of SASA, Belgrade, Serbia,*

²*Vinča Institute of Nuclear Sciences, University of Belgrade, Belgrade, Serbia,*

³*Faculty of Technology and Metallurgy, University of Belgrade, Belgrade, Serbia*

Recently lithium iron orthosilicate, $\text{Li}_2\text{FeSiO}_4$, has been found to display attractive electrochemical properties when used as cathode material. Because its constituent elements are non-toxic, low-cost and abundant, it is also attractive system from the standpoint of environmental sustainability. $\text{Li}_2\text{FeSiO}_4$ compounds are known to exhibit a rich polymorphism and several crystal structures have been reported in the literature. Due to its complex polymorphism it is still a challenge obtaining a phase pure material. Here we report the properties of pure $\text{Li}_2\text{FeSiO}_4$ obtained by solid-state reaction at 750 °C. It was found that $\text{Li}_2\text{FeSiO}_4$ crystallizes in monoclinic $P2_1/n$ space group. In this structure one set of LiO_4 tetrahedra are arranged in edge sharing pairs with FeO_4 tetrahedra, while the other set of LiO_4 tetrahedra forms edge sharing pairs with itself. In addition, galvanostatically cycled material was characterized in terms of structural and transport properties.