# Serbian Ceramic Society Conference ADVANCED CERAMICS AND APPLICATION

Organized by
Serbian Ceramic Society
&
Institute of Technical Sciences of SASA

# PROGRAM AND THE BOOK OF ABSTRACTS

Serbian Academy of Sciences and Arts, Knez Mihailova 35 May 10-11th, 2012, Belgrade, Serbia **Book title:** Serbian Ceramic Society Conference - ADVANCED CERAMICS AND APPLICATION: Program and the Book of Abstracts

#### **Publisher:**

Serbian Ceramic Society

#### **Editors**:

Prof. Dr. Vojislav Mitić Dr. Nina Obradović Dr. Lidija Mančić

### **Technical Editor:**

Aleksandra Stojičić

### **Printing:**

Serbian Academy of Sciences and Arts, Knez Mihailova 35, Belgrade, Serbia Format Pop Lukina 15, Belgrade, Serbia

#### **Edition:**

70 copies

CIP - Каталогизација у публикацији Народна библиотека Србије, Београд

666.3/.7(048) 66.017/.018(048)

SERBIAN Ceramic Society. Conference (1; 2012; Beograd)

Advanced Ceramics and Application: program and the book of abstracts / #[1st] #Serbian Ceramic Society Conference, May 10-11th, 2012, Belgrade, Serbia; organized by Serbian Ceramic Society & Institute of Technical Science of SASA; [editors Vojislav Mitić, Nina Obradović, Lidija Mančić]. - Belgrade: Serbian Ceramic Society, 2012 (Belgrade: Serbian Academy of Sciences and Arts). - XII, 37 str.; 29 cm

Tiraž 70.

#### ISBN 978-86-915627-0-0

- 1. Srpsko keramičko društvo (Beograd)
- а) Керамика Апстракти b) Наука о материјалима Апстракти c) Наноматеријали Апстракти

COBISS.SR-ID 190546188

P01

## **Electrical Properties of Sintered Magnesium- titanate Ceramics**

S. Filipović<sup>1</sup>, N. Obradović<sup>1</sup>, M. Šćepanović<sup>2</sup>, V.B. Pavlović<sup>1</sup>, V. Paunović<sup>3</sup>

Mixtures of MgO and TiO<sub>2</sub> were mechanically activated in a planetary ball mill for different time intervals. Thus obtained powders were sintered in a furnace for 2 h at temperature of 1300  $^{\circ}$ C in air atmosphere. Raman scattering spectroscopy at room temperature has been used for characterization of sintered samples. Very similar spectra for all samples were observed, which indicate that there has been structure recovery during treatment at higher temperature. SEM analyses were performed in order to investigate effect of activation and sintering process on microstructure. Electrical measurements showed difference in dielectric constant ( $\epsilon_r$ ), loss tangent (tg $\delta$ ) and specific resistance ( $\rho$ ) as a function of time of mechanical treatment. The aim of this paper was to determine optimal parameters for materials preparation with a goal to obtain dense ceramic with appropriate characteristic.

<sup>&</sup>lt;sup>1</sup>Institute of Technical Sciences of SASA, Knez Mihailova 35/IV, 11000 Belgrade, Serbia, <sup>2</sup>Institute of Physics, University of Belgrade, Pregrevica 118, 11080 Belgrade, Serbia, <sup>3</sup>Faculty for Electronics, University of Niš, Aleksandra Medvedeva 14, 18000 Niš, Serbia