



ICOM 2011

Book of abstracts

Welcome

It is our great pleasure to welcome you at the International Congress on Membranes and Membrane Processes (ICOM 2011) organized by the Membrane Technology Group of the University of Twente, The Netherlands and held at the RAI convention center in Amsterdam from July 23-29, 2011.

We tried to compose an interesting and inspiring program covering the broad spectrum of topics in the field of membrane science and technology. We invited three plenary speakers from areas closely related to, though still at a certain distance from the field of membranes, to broaden the scope of the program and generate discussion and new insights. The program covers 78 keynote lectures at the start of each conference session, giving an overview of the past and future developments in that specific field. Next to that, it consists of almost 400 oral and more than 600 posters presentations, from students as well as from senior scientists in the field.

The social program includes a welcome reception and an exclusive boat tour from the convention center, through the canals of the old city of Amsterdam, to the former stock exchange building where the conference dinner will take place.

We would like to take the opportunity to express our sincere gratitude to the members of the organizing committee for all their efforts and altruistic support at the expense of their own work. Thank you very much. Without your help, ICOM 2011 would not have been possible!

We are very grateful to our sponsors and we highly value their financial support. Finally we would like to thank all members of the membrane community for their contributions and help to make this conference a success. We appreciate your input.

We wish you a wonderful ICOM 2011 and hope you will have a great time!

Kindest regards,

Kitty Nijmeijer
Antoine Kemperman
Matthias Wessling

Chairs ICOM 2011

UNIVERSITY OF TWENTE.

Organization

Chairs

Kitty Nijmeijer
Antoine Kemperman
Matthias Wessling

Administrative support

Congress Association Twente
Jacqueline van der Lek

Organizing committee

Miriam Gironès
Greet Kamminga
Enver Güler
Harro Mengers
Elif Karatay
Olga Kattan
Beata Koziara
Irdham Kusumawardhana
Jeroen Ploegmakers
Wojciech Ogieglo
Yusuf Wibisono

Scientific Committee

Pierre Aimar
Mihai Barboiu
Laurent Bazinet
Georges Belfort
Dibakar Bhattacharyya
Cristiano Borges
Vicky Chen
Neal Chung
Joao Crespo
Zhanfeng Cui
Enrico Drioli
Eric Favre
Benny Freeman
Lidietta Giorno
Michael Guiver
May-Britt Hagg
Anita Hill

Wanqin Jin
Gunnar Jonsson
Yong Soo Kang
Freek Kapteijn
Anastasios Karabelas
Geert-Henk Koops
Bill Koros
Bernd Krause
Young Moo Lee
TorOve Leiknes
Jerry Lin
Glenn Lipscomb
Andrew Livingston
Thomas Melin
Dieter Melzner
Richard Noble
Yoram Oren

Klaus-Viktor Peinemann
Ingo Pinnau
Peter Pintauro
Gerald Pourcelly
Mary Rezac
Jesus Santa Maria
Giulio Sarti
Raphael Semiat
Toshinori Tsuru
Mathias Ulbricht
Ivo Vankelecom
Jörg Vienken
Vladimir Volkov
Nico van der Vegt
Hans Wijmans
Andrew Zydney

Proton conducting membranes based on photopolymerizable monomers

Michael Kellner¹, Philip Radovanovic², Robert Liska¹, Jovan Matovic²

¹Vienna University of Technology, Institute of Applied Synthetic Chemistry, Vienna, AT, ²Vienna University of Technology, Institute of Sensor and Actuator Systems, Vienna, AT

The proton exchange barrier or Proton Exchange Membrane (PEM) is the critical part of a fuel cell. The basic function of the membrane is to enable proton transport, while being simultaneously impermeable for electrons and gas. Typically, membranes for the PEM fuel cells (PEMFC) are made of perfluorocarbon-sulfonic acid monomers. The best known material of this class is Nafion which has a unique interpenetrating structure of hydrophobic perfluorocarbon regions providing thermal and chemical resistance, mechanical strength and diffusional resistance combined with hydrophilic regions of water clusters surrounding charged sulfonic acid groups which allow selective proton transport. For these reasons, Nafion is still considered the benchmark against

which most of the new materials are compared [1].

At the molecular level, proton transport may follow two principal mechanisms: (a) diffusion mechanism via H_3O^+ ion as a carrier and (b) proton hopping mechanism (Grotthuss transport) [2]. Contemporary PEMFCs are exclusively based on the vehicle mechanism.

PEMFCs produce water as a by-product and H^+ ions moving from the anode to the cathode pull water molecules by an electro-osmotic drag force. In addition, membrane suffers from evaporation of water at working temperatures of 60 - 90°C. Nafion effectively conducts protons only when imbibed by water within a narrow range, which limits the operating temperature of PEM fuel cells to around 80°C. However an operating temperature above 100° C is a highly desirable goal. PEM membranes are not dimensionally stable since the material significantly swells upon water absorption. Therefore the aim of our proton conducting membrane is a rigid polymer with perpendicular nano channels which are filled with a conducting sulfonic polymer where conductivity is mainly achieved by the Grotthuss mechanism.

Several monomers and crosslinker in a broad range of concentrations in water and 1-Methyl-2-pyrrolidone (NMP) respectively were screened for their mechanical properties, water uptake and conductivity in porous membranes by photo polymerization with a polar photo initiator. As conductive polymer, primarily poly(2-acrylamido-2-methylpropane sulfonic acid) (PAMPS) and poly(2-sulfoethyl methacrylate) (PSEM) respectively as well as polymers of phosphonic acid containing monomers or newly synthesized monomers were used. The conductive monomers were crosslinked with varying hydrophobic and hydrophilic multifunctional monomers like N,N'-methylene bisacrylamide (MBA), 2-Propenoic acid, 2-methyl-, 1,1'-(1,10-decanediyl) ester (D3MA) or polyethyleneglycol diacrylates with two varying chainlengths (PEG-DA700, PEG-DA330).

The advantage of several different building blocks with known characteristics is the possibility to tune the polymer to special needs of an application. For example, some polymer compositions have good conductivity at lower temperatures whereas other polymers develop better properties at elevated temperatures.

The research leading to these results has received funding from the European Community's FP7- NMP Programme, under the Project Acronym MultiPlat and with Grant Agreement: N 228943 and the Austrian Federal Ministry of Science and Research. We thank 3M for providing us with samples of the PP membrane.

1/Hamrock, S.J. and M.A. Yandrasits, *Proton Exchange Membranes for Fuel Cell Applications*. 2006. **46**(3): p. 219 - 244.

2/ Hoogers, G., *Membranes and Ionomers*, in *Fuel Cell Technology Handbook* G. Hoogers, Editor. 2002, CRC Press. p. 360