

Serbian Ceramic Society Conference ADVANCED CERAMICS AND APPLICATION VIII New Frontiers in Multifunctional Material Science and Processing

Serbian Ceramic Society
Institute of Technical Sciences of SASA
Institute for Testing of Materials
Institute of Chemistry Technology and Metallurgy
Institute for Technology of Nuclear and Other Raw Mineral Materials

PROGRAM AND THE BOOK OF ABSTRACTS

Serbian Ceramic Society Conference ADVANCED CERAMICS AND APPLICATION VIII New Frontiers in Multifunctional Material Science and Processing

Serbian Ceramic Society
Institute of Technical Science of SASA
Institute for Testing of Materials
Institute of Chemistry Technology and Metallurgy
Institute for Technology of Nuclear and Other Raw Mineral Materials

PROGRAM AND THE BOOK OF ABSTRACTS

Book title: Serbian Ceramic Society Conference - ADVANCED CERAMICS AND APPLICATION VIII Program and the Book of Abstracts

Publisher:

Serbian Ceramic Society

Editors:

Prof.dr Vojislav Mitić Dr Lidija Mančić Dr Nina Obradović

Technical Editors:

Dr Ivana Dinić Dr Marina Vuković

Printing:

Serbian Ceramic Society, Belgrade, 2019

Edition:

100 copies

CIP - Каталогизација у публикацији Народна библиотека Србије, Београд

666.3/.7(048) 66.017/.018(048)

SRPSKO keramičko društvo. Conference Advanced Ceramics and Application: New Frontiers in Multifunctional Material Science and Processing (8; 2019; Beograd)

Program; and the Book of abstracts / Serbian Ceramic Society Conference Advanced Ceramics and Application VIII: New Frontiers in Multifunctional Material Science and Processing, Serbia, Belgrade, 23-25. September 2019.; [organized by] Serbian Ceramic Society ... [etc.]; [editors Vojislav Mitić, Lidija Mančić, Nina Obradović]. - Belgrade: Serbian Ceramic Society, 2019 (Belgrade: Serbian Ceramic Society). - 98 str.: ilustr.; 30 cm

Tiraž 100.

ISBN 978-86-915627-7-9

а) Керамика -- Апстракти б) Наука о материјалима -- Апстракти в) Наноматеријали -- Апстракти

COBISS.SR-ID 279041804

properties toward the removal of MB dye during dark and visible light conditions. This finding is attributed to the presence of titanium particles coated the surface of CX-CNTs which act as active sites.

Acknowledgment: This study was realized within the frame of inter-academic collaboration between Physical Chemistry Department, National Research Centre, Giza, Egypt and Institute of Catalysis of the Bulgarian Academy of Sciences, by the project "Synthesis and Characterization of Nanocarbons Materials Loaded catalysts as nanocomposites for wastewater treatment".

P32

Characterisation and optical properties of unmodified and modified CdSe/ZnS quantum dots in pol(methyl-methacrylate) and 3-mercaptopropyltrimethoxysilane

Zorica Ž. Lazarević¹, Rouaida Mohamed Abozaid², Vesna Radojević², Nebojša Ž. Romčević¹

¹Institute of Physics, University of Belgrade, Pregrevica 118, Zemun, Belgrade, Serbia

²Faculty of Technology and Metallurgy, University of Belgrade, Belgrade, Serbia

The aim of this work is characterization of polymer nanocomposites based on poly (methyl methacrylate) (PMMA) matrix with embedded core-shell CdSe/ZnS quantum dots (QD`s). The modification of CdSe/ZnS quantum dots in PMMA interface was achieved with 3-mercaptopropyltrimethoxysilane (MPTMS). The optical properties and fluorescence of nanocomposite were investigated as consequence of interface modification. The optical properties were analyzed through FTIR and Raman. In polymer nanocomposite was established dipole-dipole bonding between S-H group of silane coupling agent and carbonyl groups of the polymer matrixes. Raman spectrum confirms a presence of alloyed layer at the coreshell interface. Time-resolved laser induced fluorescence measurements confirmed slight blue shift in CdSe/ZnS quantum dots in PMMA composite without interface modification, while there was a slight red shift with modified particles. Oxidation effects in quantum dots were removed with the use of PMMA as a host, and the core remained active, which was confirmed with FTIR analysis and time-resolved laser induced fluorescence measurements.

P33

Generalized Lorentz model description-Caputo-Fabrizio fractional derivative approach, of electrical, dielectric, conductive and magnetic processes in materials

Mohsan S A Eldakli¹, Zoran B. Vosika², Vojislav V. Mitić ^{2,3}, Goran Lazović⁴, Vesna Paunović²

Aleksandra Medvedeva 14, Niš, Serbia

In this study, generalized Lorentz model is basic one-particle model in the framework of dielectric, conductive and/or magnetic responses of materials.

AC conductivity studies of various $BaTiO_3$ or similar ceramics produced equivalent circuits with impedance spectra, usually within the framework of RCPE elements serial connection (CPE - constant phase element) or Cole element. This element, in the generalized Lorentz model, corresponds to Čaputo fractional derivative, who, as operator, contains a singular integral kernel in itself. However, in the literature,

¹ University of Zawia , Faculty of Science , Physics department, Az Zawiyah, Libya

²University of Niš, Faculty of Electronic Engineering,

³Institute of Technical Sciences of SASA, Belgrade, Serbia, Knez Mihailova 35/IV

⁴University of Belgrade, Faculty of Mechanical Engineering, Belgrade, Serbia

fractional derivatives with a non singular integral kernels have recently emerged. One of them is a Caputo-Fabrizio fractional derivative.

In this work, physical basics and all three behaviors (dielectric, conductive and magnetic) of materials and their relationships are considered in the case of electric or magnetic alternate fields, which are the tools for experimental measurements.

P34

Comparative Studies of BCY15 /Ni-Cu and BCY15 /Ni Cermet by Impedance Spectroscopy

E. Mladenova¹, M. Gabrovska², D. Nikolova², D. Vladikova¹, B. Burdin, Z. Stoynov¹

¹Acad. Evgeni Budevski Institute of Electrochemistry and Energy Systems, Bulgarian Academy of Sciences, Acad. G. Bonchev Str., Bl. 10, 1113 Sofia, Bulgaria

²Institute of Catalysis, Bulgarian Academy of Sciences, Acad. G. Bonchev Str., Bl. 11, 1113 Sofia, Bulgaria

Yttrium-doped barium cerate (BCY15) with perovskite-type structure was used for the preparation of Ni-based BCY15 anode for proton conducting solid oxide fuel cell (pSOFC).

A low-temperature wet chemical approach for integration of Ni or Ni/Cu metallic particles in BCY15 was introduced aiming to avoid the traditional ceramic high-temperature processes. The bimetallic (BCY15/Ni-Cu) and monometallic (BCY15/Ni) powders were characterized by different physical-chemical methods. The electrochemical characterization of the produced cermet was performed by impedance spectroscopy.

The purpose of this work is a deeper insight into the electrochemical performance of the anode materials obtained by the new preparation approach and evaluation of its effectiveness. The kernel is the metallic phase oxidation level during the sintering step performed at high temperature (1250°C) in air. For this purpose comparative study of the reduction process which follows the high temperature sintering was carried out. The analysis of the results shows that in the bimetallic anode electronic conductivity is registered before the reduction while in the Ni-based BCY15 cermet no electronic conductivity is observed. This result shows that the presence of highly conductive Cu brings to lower oxidation which opens possibility for introduction of the wet chemical approach in the preparation of pSOFC.

Acknowledgment: This work was partially supported by the Bulgarian Ministry of Education and Science under the National Research Programme "E+: Low Carbon Energy for the Transport and Household" approved by D01# 214/2018 and by National Infrastructure NI SEVE approved by D01# 160/28.08.18).