

SIXTEENTH ANNUAL CONFERENCE

YUCOMAT 2014

Hunguest Hotel Sun Resort Herceg Novi, Montenegro,
September 1-5, 2014
<http://www.mrs-serbia.org.rs>

Programme and The Book of Abstracts

Organised by:
Materials Research Society of Serbia

Endorsed by:
**Federation of European Material Societies
and
Materials Research Society**

Title: THE SIXTEENTH ANNUAL CONFERENCE
YUCOMAT 2014
Programme and The Book of Abstracts

Publisher: Materials Research Society of Serbia
Knez Mihailova 35/IV, 11000 Belgrade, Serbia
Phone: +381 11 2185-437; Fax: + 381 11 2185-263
<http://www.mrs-serbia.org.rs>

Editors: Prof. Dr. Dragan P. Uskoković and Prof. Dr. Velimir Radmilović

Technical editor: Aleksandra Stojičić

Cover page: Aleksandra Stojičić and Milica Ševkušić
Back cover photo: Author: Rudolf Getel
Source: Flickr (www.flickr.com/photos/rudolfgetel/4280176487)
Licence: CC BY 2.0

Copyright © 2014 Materials Research Society of Serbia

Acknowledgments: This conference is held in honour of Prof. Dragan Uskoković's 70th birthday.



Printed in: Biro Konto
Sutorina bb, Igalo – Herceg Novi, Montenegro
Phones: +382-31-670123, 670025, E-mail: bkonto@t-com.me
Circulation: 220 copies. The end of printing: August 2014

P.S.A.7

**INFLUENCE OF DIFERENT POISSON'S COEFFICIENTS OF ADHERENTS ON
STRESS DISTRIBUTION IN THE CASE OF STEP COMPOSITE JOINT**

Abdurrahman O. Houssein

Al jabel Algharbi university, Dean of Faculty of engineering - Jadoo, Libya

The influences of Poisson's coefficients the case of step joint of two composite plates are analyzed using the finite element method. Geometry of the joint, boundary condition and type as well as amount of loading can be varied as per the requirement. Method also allows varying the properties of adherents and adhesives that include modulus of elasticity, Poisson's ratio as well as allowable stress values. Mesh size is

The results show the places where the maximum normal and shear stresses occur. It is interesting to note that the variations of stress values in the x direction is small when compared with x and y directions.

Key words: composite plates, finite element analysis, step joint.

P.S.A.8

**SYNTHESIS OF LiFePO_4 BY MECHANICAL STRESSING
AND THERMAL ANNEALING**

Miloš Milović¹, D. Jugović¹, M. Mitrić², N. Cvjetičanin³,
A. Mraković², M. Senna⁴, D. Uskoković¹

¹*Institute of Technical Sciences of SASA, Belgrade, Serbia,* ²*Vinča Institute of Nuclear Sciences, University of Belgrade, Belgrade, Serbia,* ³*Faculty of Physical Chemistry, University of Belgrade, Belgrade, Serbia,* ⁴*Faculty of Science and Technology, Keio University, 3-14-1 Hiyoshi, Kohoku-ku, Yokohama, Japan*

Mechanical activation can be regarded as a multi-step process with changes in the energetic parameters and the amount of accumulated energy of solids in each step. Here we report the influence of mechanochemical processing on the synthesis of LiFePO_4 powders. The different precursor powders were milled in a planetary mill by using WC vials and 5 mm balls made of the same material. A slightly reductive atmosphere ($\text{Ar} + 5\% \text{H}_2$) was used in both mechanical stressing and thermal annealing so as to prevent the oxidation of iron. All synthesis steps were followed by an X-ray diffractometry and FT-IR spectroscopy. The results were compared with previous findings of precipitated and annealed powder, without mechanochemical treatment.