## National Academy of Sciences of Ukraine (NASU) Frantsevych Institute for Problems of Materials Science of NASU National Technical University of Ukraine "KPI" Ukrainian Materials Science Society INTEM LTD

## THE SECOND INTERNATIONAL SAMSONOV MEMORIAL CONFERENCE

## "MATERIAL SCIENCE OF REFRACTORY COMPOUNDS"

**CONFERENCE ABSTRACTS** 

May 18-20, 2010 Kyiv, Ukraine

## Influence of mechanical activation on electrical properties of sintered barium-zinc-titanate ceramics

Nina Obradovic<sup>1</sup>, Suzana Filipovic<sup>1</sup>, Miodrag Mitric<sup>2</sup>, Vladimir Pavlovic<sup>3</sup>, Vesna Paunovic<sup>4</sup>, Momcilo M. Ristic<sup>5</sup>

<sup>1</sup>Institute of Technical Sciences SASA, Knez-Mihajlova 35/IV,11000 Belgrade, Serbia

<sup>2</sup>The Vinca Institute of Nuclear Sciences, Mike Alasa 14-16, 11000 Belgrade, Serbia

<sup>3</sup>Faculty for Agriculture, University of Belgrade, 11000 Belgrade, Serbia

<sup>4</sup>Faculty for Electronics, University of Nis, 18000 Nis, Serbia

<sup>5</sup>Serbian Academy of Sciences and Arts, Knez-Mihajlova 35, 11000 Belgrade, Serbia

Starting mixtures of BaCO<sub>3</sub>, ZnO and TiO<sub>2</sub> powders were mechanically activated in a planetary ball mill for various periods of time. The powders obtained were sintered non-isothermally to temperatures between 1100 and 1300°C and then held at those temperatures for 120 min. Results of structural characterization using X-ray powder

diffraction method, DTA analyses and SEM analyses were conducted for activated and sintered samples. These results were correlated with the results of electric resistivity, capacitance and loss tangent of the samples and it was found that with increasing in milling time, the increase in values of electrical properties was noticed.